AT-KS adapter grommets

based on KT large, for Keystone couplers



The grommet AT-KS is constructed on the basis of a large KT cable grommet. The polyamide body is moulded with elastomer.

The cut-out enables a snap-in assembly of all couplers based on the Keystone system. If required the keystone couplers can be disassembled with a screwdriver.

The insertion of AT-KS into an icotek cable entry frame enables the routing of cables with and without connectors in combination with the creation of interfaces for <u>Keystone couplers</u> within one cable entry system. Separate cut-outs for connectors are no longer necessary.

AT-KS provides ingress protection of up to IP54 (depending on the Keystone coupler type and manufacturer).

Specifications

IP rating (EN 60529)	IP54
Material	Elastomer Body: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free

Advantages & benefits

- Connectors can be integrated directly into the cable entry frame
- Separate cut-outs for connectors are no longer necessary
- Space-saving solution
- Adapter grommet is suitable for more than 70 different Keystone jacks
- Snap-in assembly

Product types & sizes

AT-KS



 Part No.
 39952

 EAN
 4251269321481

 Package quantity
 10

 Length
 42 mm

 Width
 41,5 mm

 Height
 19 mm

 Mounting height
 2 mm

Keystone jack

AT-KS-USB 3.0



Part No.
EAN
Package quantity
Length
Width
Height
Mounting height

39968 4251269325151 1 42 mm 41,5 mm 19 mm 2 mm Keystone jack

USB 3.0



Part No.

Package quantity Length Width

Height Mounting height 39981

4251269335259

42 mm 41,5 mm 19 mm 2 mm

Keystone jack

USB-C

AT-KS-HDMI



Part No. EAN

Package quantity Length

Width Height

Mounting height

39969

4251269325168

1 42 mm 41,5 mm 19 mm

2 mm

Keystone jack

HDMI 2.1

AT-KS-CAT6



Part No.

EAN

Package quantity

Length Width Height

Mounting height

39970


4251269325175

1 42 mm 41,5 mm 19 mm 2 mm

Keystone jack

CAT6a

AT-KS-CAT7



Part No.

EAN

Package quantity

Length Width Height Mounting height 39983

4251269336409

1 42 mm 41,5 mm 19 mm 2 mm

Keystone jack

CAT7

