

KTMB 183 | Multi-range grommets for KEL 183

for cable diameters 34 - 75 mm / IP54 / UL Type 12



The grommets KTMB-P to KTMB-S are suitable for cable diameters up to 75 mm. These grommets can be used with the [KEL 183 cable entry frames](#).

These multi-range grommets are not split and have a defined area for pushing the cable through.

The blank grommet KTMB-O can accept cable sizes within a specified range. The membrane of the KTMB-O can be pierced or cut (cable diameter minus 10 mm) for cables up to 55mm in diameter.



Specifications


IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	halogen free, silicone free

Advantages & benefits

- Installation of cables up to 75 mm in diameter
- It is possible to install rigid cables at angles


Product types & sizes

KTMB-O




Part No.	41410	Mounting height	2 mm
EAN	4251269307133	Blank grommet	1
Package quantity	1	Clamping range	Blank grommet
Colour	grey (similar RAL 7035)		
Length	91 mm		
Width	86 mm		
Height	19 mm		

KTMB-P



Part No.	41415	Height	19 mm
EAN	4251269307140	Mounting height	2 mm
Package quantity	1	For cable type	Round cable
For max. no. of cables	1	Clamping range	34 - 44 mm
Colour	grey (similar RAL 7035)	Clamping range	1 x 34 - 44 mm
Length	91 mm		
Width	86 mm		


KTMB-Q

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41420
4251269307157
1
1
grey (similar RAL 7035)
91 mm
86 mm

Height
Mounting height
Clamping range
Clamping range

19 mm
2 mm
44 - 54 mm
1 x 44 - 54 mm


KTMB-R

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41425
4251269307164
1
1
grey (similar RAL 7035)
91 mm
86 mm

Height
Mounting height
For cable type
Clamping range
Clamping range

19 mm
2 mm
Round cable
54 - 64 mm
1 x 54 - 64 mm

KTMB-S

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41430
4251269307171
1
1
grey (similar RAL 7035)
91 mm
86 mm

Height
Mounting height
For cable type
Clamping range
Clamping range

19 mm
2 mm
Round cable
64 - 75 mm
1 x 64 - 75 mm