

# QTMB | Multi-range cable grommets for QUICK systems

for cable diameters 14 - 29 mm / IP54



The QTMB range for pre-terminated cables is used with the following cable entry frames:

- [KEL-QUICK](#)
- [QVT-CLICK](#)

The innovative membrane enables the routing of cables with diameters that can vary up to 3 mm.

For the first time, utilising the QTMB, even large cables with cable diameters from 14 to 29 mm can be routed.

[ST-B Plugs](#) can be used for sealing the grommets if cables have been removed.

IP54

HL3  
EN 45545-2

ECOLAB  
certified

UV  
ISO 4892-2A

PNEUMATICS

RoHS  
compliant

REACH  
COMPLIANCE

Made in  
Germany

## Specifications


IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free

## Advantages & benefits

- Routing of cables with and without connectors
- Only 7 grommets cover a clamping range from 14 to 29 mm
- Innovative wave cut for a better sealing
- Innovative membrane for high flexibility


## Product types & sizes

### QTBG




Part No.	<b>42545</b>	Mounting height	<b>2 mm</b>
EAN	<b>4251269321634</b>	Blank grommet	<b>1</b>
Package quantity	<b>10</b>	Clamping range	<b>Blank grommet</b>
Colour	<b>grey (similar RAL 7035)</b>		
Length	<b>40 mm</b>		
Width	<b>39 mm</b>		
Height	<b>17 mm</b>		


### QTMB 14-17




Part No.	<b>42515</b>	Height	<b>17 mm</b>
EAN	<b>4251269321603</b>	Mounting height	<b>2 mm</b>
Package quantity	<b>10</b>	For cable type	<b>Round cable</b>
For max. no. of cables	<b>1</b>	Clamping range	<b>14 - 17 mm</b>
Colour	<b>grey (similar RAL 7035)</b>	Clamping range	<b>1 x 14 - 17 mm</b>
Length	<b>40 mm</b>		
Width	<b>39 mm</b>		

**QTMB 16-19**


Part No.	<b>42516</b>	Height	<b>17 mm</b>
EAN	<b>4251269321986</b>	Mounting height	<b>2 mm</b>
Package quantity	<b>10</b>	For cable type	<b>Round cable</b>
For max. no. of cables	<b>1</b>	Clamping range	<b>16 - 19 mm</b>
Colour	<b>grey (similar RAL 7035)</b>	Clamping range	<b>1 x 16 - 19 mm</b>
Length	<b>40 mm</b>		
Width	<b>39 mm</b>		

**QTMB 18-21**


Part No.	<b>42517</b>	Height	<b>17 mm</b>
EAN	<b>4251269321610</b>	Mounting height	<b>2 mm</b>
Package quantity	<b>10</b>	For cable type	<b>Round cable</b>
For max. no. of cables	<b>1</b>	Clamping range	<b>18 - 21 mm</b>
Colour	<b>grey (similar RAL 7035)</b>	Clamping range	<b>1 x 18 - 21 mm</b>
Length	<b>40 mm</b>		
Width	<b>39 mm</b>		

**QTMB 20-23**


Part No.	<b>42518</b>	Height	<b>17 mm</b>
EAN	<b>4251269321627</b>	Mounting height	<b>2 mm</b>
Package quantity	<b>10</b>	For cable type	<b>Round cable</b>
For max. no. of cables	<b>1</b>	Clamping range	<b>20 - 23 mm</b>
Colour	<b>grey (similar RAL 7035)</b>	Clamping range	<b>1 x 20 - 23 mm</b>
Length	<b>40 mm</b>		
Width	<b>39 mm</b>		

**QTMB 22-25**

Part No.	<b>42519</b>	Height	<b>17 mm</b>
EAN	<b>4251269322723</b>	Mounting height	<b>2 mm</b>
Package quantity	<b>10</b>	For cable type	<b>Round cable</b>
For max. no. of cables	<b>1</b>	Clamping range	<b>22 - 25 mm</b>
Colour	<b>grey (similar RAL 7035)</b>	Clamping range	<b>1 x 22 - 25 mm</b>
Length	<b>40 mm</b>		
Width	<b>39 mm</b>		

**QTMB 24-27**

Part No.	<b>42520</b>	Height	<b>17 mm</b>
EAN	<b>4251269322730</b>	Mounting height	<b>2 mm</b>
Package quantity	<b>10</b>	For cable type	<b>Round cable</b>
For max. no. of cables	<b>1</b>	Clamping range	<b>24 - 27 mm</b>
Colour	<b>grey (similar RAL 7035)</b>	Clamping range	<b>1 x 24 - 27 mm</b>
Length	<b>40 mm</b>		
Width	<b>39 mm</b>		

**QTMB 26-29**

Part No.	<b>42521</b>	Height	<b>17 mm</b>
EAN	<b>4251269322747</b>	Mounting height	<b>2 mm</b>
Package quantity	<b>10</b>	For cable type	<b>Round cable</b>
For max. no. of cables	<b>1</b>	Clamping range	<b>26 - 29 mm</b>
Colour	<b>grey (similar RAL 7035)</b>	Clamping range	<b>1 x 26 - 29 mm</b>
Length	<b>40 mm</b>		
Width	<b>39 mm</b>		

