AT-KS-AK adapter grommets

based on KT large, for Keystone couplers, with protection cover / IP54



The grommet AT-KS-AK is constructed on the basis of a large KT cable grommet. The polyamide body is moulded with elastomer.

The cut-out enables a snap-in assembly of all couplers based on the Keystone system. If required the keystone couplers can be disassembled with a screwdriver.

The interface can be closed and even sealed using the protective cover on the front of the grommet.

The insertion of AT-KS-AK into an icotek cable entry frame enables the routing of cables with and without connectors in combination with the creation of interfaces for Keystone couplers within one cable entry system. Separate cut-outs for connectors are no longer necessary.

AT-KS-AK fulfills protection classes up to IP54 when the flap is closed (regardless of the keystone module type and manufacturer).

Specifications

		Connectors can be integrated directly into the cable entry frame
IP rating (EN 60529)	IP54	Connectors can be integrated directly into the cable entry frame
.		Separate cut-outs for connectors are no longer necessary
Material	Elastomer Body: Polyamide	Adapter grommet is suitable for more than 70 different Keystone ja
		Certified protection class IP54 (according to EN 60529) when cover
Flame class	UL94-V0, self-extinguishing	Cover can be fixed when opened
Operating temperature	-40 C° to 100 C°	The interface can be secured by sealing
Properties	silicone free, halogen free	Space-saving solution

Product types & sizes

AT-KS-AK	Part No. EAN Package quantity Length Width Height Mounting height	39967 4251269335150 10 42 mm 41,5 mm 25,3 mm 6,3 mm	Keystone jack	-	
AT-KS-AK-USB 3.0	Part No. EAN Package quantity Length Width Height Mounting height	39977 4251269335174 1 42 mm 41,5 mm 25,3 mm 6,3 mm	Keystone jack	USB 3.0	

Advantages & benefits

	Connectors can be integrated directly into the cable entry frame			
	Separate cut-outs for connectors are no longer necessary			
	Adapter grommet is suitable for more than 70 different Keystone jacks			
	Certified protection class IP54 (according to EN 60529) when cover is closed			
juishing	Cover can be fixed when opened			
	The interface can be secured by sealing			
en free	Space-saving solution			
	Snap-in assembly			

IP54 ^O	Part No. EAN Package quantity Length Width Height Mounting height	39980 4251269335204 1 42 mm 41,5 mm 25,3 mm 6,3 mm	Keystone jack	USB-C
AT-KS-AK-HDMI	Part No. EAN Package quantity Length Width Height Mounting height	39978 4251269335181 1 42 mm 41,5 mm 25,3 mm 6,3 mm	Keystone jack	HDMI 2.1
AT-KS-AK-CAT6	Part No. EAN Package quantity Length Width Height Mounting height	39979 4251269335198 1 42 mm 41,5 mm 25,3 mm 6,3 mm	Keystone jack	CAT6a
AT-KS-AK-CAT7	Part No. EAN Package quantity Length Width Height Mounting height	39982 4251269336393 1 42 mm 41,5 mm 25,3 mm 6,3 mm	Keystone jack	CAT7

