

# KEL-JUMBO | Split cable entry frames

for cables with diameters of up to 65 mm / IP54 / UL Type 12



The KEL-JUMBO cable entry system for installation of cables and conduits with a diameter of up to 65 mm, especially suited for supply cables. The innovative grommet design with the flex-membrane provides flexing and adjustment of the position for larger and more rigid cables.

We recommend round cut-outs, which can be made using standard knockout tools. Suggested cut-out: cable diameter +15 - 20%.

A flat rubber gasket is included in the shipment.

IP54

UL TYPE  
12

UL  
US

RI  
A

HL3  
EN 45545-2

EN 61373

ECOLAB  
certified

UV  
ISO 4892-2A

RoHS  
compliant

REACH  
COMPLIANCE

Made in  
Germany


## Specifications


IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	vibration proof, UV-resistant, silicone free, anti-corrosive (V2A versions), halogen free
Mounting options	Screw type mounting
Mounting height	35 mm


## Advantages & benefits

- Installation of cables up to 65 mm in diameter
- It is possible to install rigid cables at angles
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Strain relief according to EN 62444

## Product types & sizes

<b>KEL-JUMBO 1</b>	Part No.	<b>42360</b>	Height	<b>35 mm</b>
	EAN	<b>4251269308550</b>	Mounting height	<b>35 mm</b>
	Package quantity	<b>1</b>	Cut-out size	<b>78 x 80.5 mm</b>
	For max. no. of cables	<b>1</b>	No. of screw holes	<b>4</b>
	Max. cable diameter	<b>65 mm</b>	Diam. of screw holes	<b>7 mm</b>
	Length	<b>110 mm</b>	Screw material	<b>Mild steel, galvanically zinc plated</b>
	Width	<b>116 mm</b>	Suitable for grommets	<b>1 x KTF</b>

<b>KEL-JUMBO 1 V2A</b>	Part No.	<b>42360.200</b>	Height	<b>35 mm</b>
	EAN	<b>4251269308567</b>	Mounting height	<b>35 mm</b>
	Package quantity	<b>1</b>	Cut-out size	<b>78 x 80.5 mm</b>
	For max. no. of cables	<b>1</b>	No. of screw holes	<b>4</b>
	Max. cable diameter	<b>65 mm</b>	Diam. of screw holes	<b>7 mm</b>
	Length	<b>110 mm</b>	Screw material	<b>Stainless steel (V2A)</b>
	Width	<b>116 mm</b>	Suitable for grommets	<b>1 x KTF</b>


**KEL-JUMBO 2**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Max. cable diameter  
Length  
Width

**42350**  
**4251269308536**  
**1**  
**2**  
**65 mm**  
**200 mm**  
**116 mm**

Height  
Mounting height  
Cut-out size  
No. of screw holes  
Diam. of screw holes  
Screw material  
Suitable for grommets

**35 mm**  
**35 mm**  
**168 x 80.5 mm**  
**4**  
**7 mm**  
**Mild steel, galvanically zinc plated**  
**2 x KTF**

**KEL-JUMBO 2 V2A**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Max. cable diameter  
Length  
Width

**42350.200**  
**4251269308543**  
**1**  
**2**  
**65 mm**  
**200 mm**  
**116 mm**

Height  
Mounting height  
Cut-out size  
No. of screw holes  
Diam. of screw holes  
Screw material  
Suitable for grommets

**35 mm**  
**35 mm**  
**168 x 80.5 mm**  
**4**  
**7 mm**  
**Stainless steel (V2A)**  
**2 x KTF**