

# KTMB 183 | Multi-range grommets for KEL 183

for cable diameters 34 - 75 mm / IP54 / UL Type 12



The grommets KTMB-P to KTMB-S are suitable for cable diameters up to 75 mm. These grommets can be used with the [KEL 183 cable entry frames](#).

These multi-range grommets are not split and have a defined area for pushing the cable through.

The blank grommet KTMB-O can accept cable sizes within a specified range. The membrane of the KTMB-O can be pierced or cut (cable diameter minus 10 mm) for cables up to 55mm in diameter.



## Specifications


<b>IP rating (EN 60529)</b>	IP54
<b>UL Type (UL 50E)</b>	UL Type 12
<b>Material</b>	Elastomer
<b>Flame class</b>	UL94-V0, self-extinguishing
<b>Operating temperature</b>	-40 C° to 100 C°
<b>Properties</b>	halogen free, silicone free

## Advantages & benefits

- Installation of cables up to 75 mm in diameter
- It is possible to install rigid cables at angles

## Product types & sizes


### KTMB-O



Part No.	<b>41410</b>
EAN	<b>4251269307133</b>
Package quantity	<b>1</b>
Colour	<b>grey (similar RAL 7035)</b>
Length	<b>91 mm</b>
Width	<b>86 mm</b>
Height	<b>19 mm</b>


Mounting height	<b>2 mm</b>
Blank grommet	<b>1</b>
Clamping range	<b>Blank grommet</b>

### KTMB-P



Part No.	<b>41415</b>
EAN	<b>4251269307140</b>
Package quantity	<b>1</b>
For max. no. of cables	<b>1</b>
Colour	<b>grey (similar RAL 7035)</b>
Length	<b>91 mm</b>
Width	<b>86 mm</b>

Height	<b>19 mm</b>
Mounting height	<b>2 mm</b>
For cable type	<b>Round cable</b>
Clamping range	<b>34 - 44 mm</b>
Clamping range	<b>1 x 34 - 44 mm</b>


**KTMB-Q**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Colour  
Length  
Width

**41420**  
**4251269307157**  
**1**  
**1**  
**grey (similar RAL 7035)**  
**91 mm**  
**86 mm**

Height  
Mounting height  
Clamping range  
Clamping range

**19 mm**  
**2 mm**  
**44 - 54 mm**  
**1 x 44 - 54 mm**


**KTMB-R**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Colour  
Length  
Width

**41425**  
**4251269307164**  
**1**  
**1**  
**grey (similar RAL 7035)**  
**91 mm**  
**86 mm**

Height  
Mounting height  
For cable type  
Clamping range  
Clamping range

**19 mm**  
**2 mm**  
**Round cable**  
**54 - 64 mm**  
**1 x 54 - 64 mm**

**KTMB-S**

Part No.  
EAN  
Package quantity  
For max. no. of cables  
Colour  
Length  
Width

**41430**  
**4251269307171**  
**1**  
**1**  
**grey (similar RAL 7035)**  
**91 mm**  
**86 mm**

Height  
Mounting height  
For cable type  
Clamping range  
Clamping range

**19 mm**  
**2 mm**  
**Round cable**  
**64 - 75 mm**  
**1 x 64 - 75 mm**