

KT-DPF | Multi-range cable grommets, grey

in pyramid shape, for cable diameters 3-26 mm / IP54 / UL Type 12



The KT-DPF grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. Due to the flexibility and unique pyramid shape, routing and flexible positioning of rigid cables is much easier compared to using conventional cable glands.

The KT-DPF grommets are not split and therefore only usable for cables without connectors.

It is recommended that additional strain relief be provided for the cables using a cable tie.

Cutting of KT-DPF grommets: Cable diameter less 20%.




Specifications


IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free


Advantages & benefits

- Large clamping range of 3 to 26 mm with only 3 grommets
- Ideal for wiring non pre-terminated cables locally
- Easy storage

Product types & sizes

KT-DPF-A gy	Part No.	41260	Height	50 mm
	EAN	4251269306730	Mounting height	33 mm
	Package quantity	10	For cable type	Round cable
	For max. no. of cables	1	attr.Klemmbereich kombiniert	3 - 12 mm
	Colour	grey (similar RAL 7035)	Clamping range	1 x 3 - 12 mm
	Length	21 mm		
	Width	21 mm		

KT-DPF-B gy	Part No.	41261	Height	59 mm
	EAN	4251269306747	Mounting height	42 mm
	Package quantity	10	For cable type	Round cable
	For max. no. of cables	1	attr.Klemmbereich kombiniert	4 - 18 mm
	Colour	grey (similar RAL 7035)	Clamping range	1 x 4 - 18 mm
	Length	41,5 mm		
	Width	42 mm		



Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41262
4251269306754
10
1
grey (similar RAL 7035)
41,5 mm
42 mm

Height
Mounting height
For cable type
attr.Klemmbereich kombiniert
Clamping range

59 mm
42 mm
Round cable
14 - 26 mm
1 x 14 - 26 mm

icotek[®]
smart cable management