

QT-DT | Multi-membrane cable grommets for QUICK systems

for cable diameters 1 - 12.2 mm / IP54



The QT-DT cable grommets can be used anywhere where a large number of electrical, pneumatic or hydraulic lines must be routed and sealed with IP54. By using the QT-DT grommets, the cable density can be significantly increased.

QT-DT grommets are compatible with split icotek cable entry frames [KEL-QUICK](#) and [KEL-QTA](#). The routing of cables with and without preassembled connectors in one cable entry frame can thus be easily combined.

The QT-DT grommets are also perfectly suitable for the assembly of subsequently terminated cable harnesses.

[ST-B Plugs](#) can be used for sealing pierced membranes if cables have been removed.

IP54

RINA

HL3
EN 45545-2

ECOLAB
certified

UV
ISO 4892-2A

PNEUMATICS

RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

Specifications


IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free

Advantages & benefits

- Routing of cables with and without connectors
- High cable density
- Cost-effective solution
- Enables sub-assembly of cable harnesses

Product types & sizes

QT-DT 1




Part No.	42550
EAN	4251269320576
Package quantity	10
For max. no. of cables	4
Colour	grey (similar RAL 7035)
Length	19 mm
Width	20 mm

Height	12 mm
For cable type	Round cable
Clamping range	4 x 1 - 6,5 mm
Clamping range	4 x 1 - 6.5 mm

Height	12 mm
For cable type	Round cable
Clamping range	4 x 1 - 6,5 mm
Clamping range	4 x 1 - 6.5 mm


QT-DT 2



Part No.	42551
EAN	4251269320583
Package quantity	10
For max. no. of cables	4
Colour	grey (similar RAL 7035)
Length	19 mm
Width	20 mm


Height	12 mm
For cable type	Round cable
Clamping range	2 x 1 - 3,5 mm 2 x 1 - 6,5 mm
Clamping range	2 x 1 - 3.5 mm

Height	12 mm
For cable type	Round cable
Clamping range	2 x 1 - 3,5 mm 2 x 1 - 6,5 mm
Clamping range	2 x 1 - 3.5 mm
Clamping range	2 x 1 - 6.5 mm

QT-DT 3


Part No. **42552**
 EAN **4251269320590**
 Package quantity **10**
 For max. no. of cables **9**
 Colour **grey (similar RAL 7035)**
 Length **19 mm**
 Width **20 mm**

Height **12 mm**
 For cable type **Round cable**
 Clamping range **9 x 1 - 3,5 mm**
 Clamping range **9 x 1 - 3.5 mm**

QT-DT 8


Part No. **42556**
 EAN **4251269322907**
 Package quantity **10**
 For max. no. of cables **14**
 Colour **grey (similar RAL 7035)**
 Length **40 mm**
 Width **39 mm**

Height **17 mm**
 For cable type **Round cable**
 Clamping range **12 x 1 - 6,5 mm | 2 x 1 - 12,2 mm**
 Clamping range **12 x 1 - 6.5 mm**
 Clamping range **2 x 1 - 12.2 mm**

QT-DT 9


Part No. **42557**
 EAN **4251269322914**
 Package quantity **10**
 For max. no. of cables **15**
 Colour **grey (similar RAL 7035)**
 Length **40 mm**
 Width **39 mm**

Height **17 mm**
 For cable type **Round cable**
 Clamping range **15 x 1 - 7,1 mm**
 Clamping range **15 x 1 - 7.1 mm**

QT-DT 10


Part No. **42558**
 EAN **4251269322921**
 Package quantity **10**
 For max. no. of cables **10**
 Colour **grey (similar RAL 7035)**
 Length **40 mm**
 Width **39 mm**

Height **17 mm**
 For cable type **Round cable**
 Clamping range **4 x 1 - 6,5 mm | 3 x 1 - 9,5 mm**
 Clamping range **4 x 1 - 6.5 mm**
 Clamping range **3 x 1 - 9.5 mm**
 Clamping range **3 x 1 - 11.3 mm**

QT-DT 11

Part No. **42559**
 EAN **4251269322938**
 Package quantity **10**
 For max. no. of cables **9**
 Colour **grey (similar RAL 7035)**
 Length **40 mm**
 Width **39 mm**

Height **17 mm**
 For cable type **Round cable**
 Clamping range **9 x 1 - 9,5 mm**
 Clamping range **9 x 1 - 9.5 mm**

QT-DT 12

Part No. **42560**
 EAN **4251269322945**
 Package quantity **10**
 For max. no. of cables **5**
 Colour **grey (similar RAL 7035)**
 Length **40 mm**
 Width **39 mm**

Height **17 mm**
 For cable type **Round cable**
 Clamping range **1 x 1 - 9,5 mm | 4 x 1 - 14,5 mm**
 Clamping range **1 x 1 - 9.5 mm**
 Clamping range **4 x 1 - 14.5 mm**

