DB Distribution Box | Split 360° cable entry system

for cables with and without connectors, M32 - M75 / IP54




With the distribution box, centrally routed cables can be distributed 360° in all desired directions.

Cables (with and without connectors) with a diameter of 1 to 15 mm can be routed, sealed and strain relieved in accordance with EN 62444.

The distribution box is suitable for metric cut-outs M32 - M75 and can be fixed with a locknut, which is included in the delivery.

When using multi grommets, up to 48 cables can be routed and a high cable density is achieved.

Thanks to the screw mount cover and the use of split cable grommets, retrofits, repairs and maintenance can be done much more easily and quickly.




Specifications

IP rating (EN 60529)	IP54
Material	Polyamide
Operating temperature	-40 C° to 140 C°
Properties	vibration proof, silicone free, halogen free
Mounting options	Fasten with locknut

Advantages & Benefits

- Fast and easy assembly
- Easy distribution of cables in a 360° angle
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Suitable for metric cut-outs M32 M75
- Strain relief according to EN 62444
- Use of the proven KT grommet system
- High cable density, wide variety of grommets
- High flexibility with the use of multi-range and IMAS-CONNECT™ adapter
- Hexagonal locknut included in the delivery
- High stability, vibration resistant
- Mechanical protection of the central entry point

Product Types & Sizes



 Part No.
 54300

 EAN
 4251269332524

 Package quantity
 5

 For max. no. of cables
 12

 Max. cable diameter
 15 mm

 Length
 72 mm

 Width
 67 mm

Height 53 mm

Mounting height 39,4 mm


Cut-out size, metric M32

Cut-out size, round 32,3 mm

Thread M32 × 1,5

Thread length 13,6 mm

Suitable for grommets 3 x KT small




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length

Width

4251269332531 5 24 15 mm 94,5 mm 87 mm

54301

DB 3×3 | M63



Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width 54302 4251269332548 1 36 15 mm 115 mm

104 mm

Height 53 mm

Mounting height 39,4 mm

Cut-out size, metric M63


Cut-out size, round 63,4 mm

Thread M63 × 1,5

Thread length 13,6 mm

Suitable for grommets 9 x KT small

DB 3×4 | M75



Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

Height 53 mm

Mounting height 39,4 mm

Cut-out size, metric M75

Cut-out size, round 75,5 mm

Thread M75 × 1,5

Thread length 13,6 mm

Suitable for grommets 12 x KT small

