

KEL-JUMBO | Split cable entry frames

for cables with diameters of up to 65 mm / IP54 / UL Type 12



The KEL-JUMBO cable entry system for installation of cables and conduits with a diameter of up to 65 mm, especially suited for supply cables. The innovative grommet design with the flex-membrane provides flexing and adjustment of the position for larger and more rigid cables.

We recommend round cut-outs, which can be made using standard knockout tools. Suggested cut-out: cable diameter +15 - 20%.

A flat rubber gasket is included in the shipment.

IP54

UL TYPE
12

UL
US

RI
A

HL3
EN 45545-2

EN 61373

ECOLAB
certified

UV
ISO 4892-2A

RoHS
compliant

REACH
COMPLIANCE

Made in
Germany


Specifications


| | |
|-----------------------|---|
| IP rating (EN 60529) | IP54 |
| UL Type (UL 50E) | UL Type 12 |
| Material | Polyamide |
| Flame class | UL94-V0, self-extinguishing |
| Operating temperature | -40 C° to 140 C° |
| Properties | vibration proof, UV-resistant, silicone free, anti-corrosive (V2A versions), halogen free |
| Mounting options | Screw type mounting |
| Mounting height | 35 mm |


Advantages & Benefits

- Installation of cables up to 65 mm in diameter
- It is possible to install rigid cables at angles
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Strain relief according to EN 62444


Product Types & Sizes

| | | | | |
|--|------------------------|----------------------|-----------------------|---|
| KEL-JUMBO 1 | Part No. | 42360 | Height | 35 mm |
|  | EAN | 4251269308550 | Mounting height | 35 mm |
| | Package quantity | 1 | Cut-out size | 78 × 80.5 mm |
| | For max. no. of cables | 1 | No. of screw holes | 4 |
| | Max. cable diameter | 65 mm | Diam. of screw holes | 7 mm |
| | Length | 110 mm | Screw material | Mild steel, galvanically zinc plated |
| | Width | 116 mm | Suitable for grommets | 1 x KTF |

| | | | | |
|--|------------------------|----------------------|-----------------------|------------------------------|
| KEL-JUMBO 1 V2A | Part No. | 42360.200 | Height | 35 mm |
|  | EAN | 4251269308567 | Mounting height | 35 mm |
| | Package quantity | 1 | Cut-out size | 78 × 80.5 mm |
| | For max. no. of cables | 1 | No. of screw holes | 4 |
| | Max. cable diameter | 65 mm | Diam. of screw holes | 7 mm |
| | Length | 110 mm | Screw material | Stainless steel (V2A) |
| | Width | 116 mm | Suitable for grommets | 1 x KTF |

KEL-JUMBO 2

| | | | |
|------------------------|----------------------|-----------------------|---|
| Part No. | 42350 | Height | 35 mm |
| EAN | 4251269308536 | Mounting height | 35 mm |
| Package quantity | 1 | Cut-out size | 168 × 80.5 mm |
| For max. no. of cables | 2 | No. of screw holes | 4 |
| Max. cable diameter | 65 mm | Diam. of screw holes | 7 mm |
| Length | 200 mm | Screw material | Mild steel, galvanically zinc plated |
| Width | 116 mm | Suitable for grommets | 2 x KTF |

KEL-JUMBO 2 V2A

| | | | |
|------------------------|----------------------|-----------------------|------------------------------|
| Part No. | 42350.200 | Height | 35 mm |
| EAN | 4251269308543 | Mounting height | 35 mm |
| Package quantity | 1 | Cut-out size | 168 × 80.5 mm |
| For max. no. of cables | 2 | No. of screw holes | 4 |
| Max. cable diameter | 65 mm | Diam. of screw holes | 7 mm |
| Length | 200 mm | Screw material | Stainless steel (V2A) |
| Width | 116 mm | Suitable for grommets | 2 x KTF |

icotek[®]
smart cable management