KVT-ER | Split cable gland

for cables with connectors, M25 - M63 / IP66 / IP68 / UL Type 12/4X*

KVT-ER are split cable glands for routing and sealing cables with connectors, with diameters from 1 to 16 mm (KT 1 - 15) and 13 to 35 mm (KTG 13 - KT 34). But also electric, pneumatic or hydraulic lines without terminals or connectors as well as corrugated conduits can be easily routed (e.g. into control panels, enclosures or machinery), sealed and strain relieved acc. to EN 62444.

The KVT-ER sizes are based on metric standard cut-outs M25, M32, M50 and M63. Hexagonal locknuts are included in the shipment. For assembly, we recommend to tighten the cover lid screws with max. 2 Nm.

Due to the injected gasket and if single-hole grommets are used, the KVT-ER provides certified protection ratings IP66/IP68 and UL type 12 & 4X*.

*4X for indoor use only

IP54	IP55	IP64	IP65	IP66	IP67
IP68	UL TYPE 12	UL TYPE 4X*	cULus	RINA	HL3 EN 45545-2
EN 61373	ECOLAB certified	Made in Germany	RoHS compliant	REACH COMPLIANCE	

Specifications

IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
UL Type (UL 50E)	UL Type 12, UL Type 4X*
Material	Body: Polypropylene Integrated sealing lip: Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 110 C°
Properties	halogen free, silicone free
Mounting options	Fasten with locknut

Advantages & Benefits

- Certified protection IP66/IP68 (acc. to EN 60529)
- Strain relief according to EN 62444
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Suitable for metric cut-outs
- Hexagonal locknut included in the delivery
- High stability, vibration resistant

Product Types & Sizes

KVT-ER 25

Part No.	**45450**	Mounting height	**20 mm**
EAN	**4251269319716**	Cut-out size, metric	**M25**
Package quantity	**10**	Cut-out size, round	**25,3 mm**
For max. no. of cables	**1**	Thread	**M25 × 1,5**
Max. cable diameter	**15 mm**	Thread length	**18 mm**
Color	**black**	Suitable for grommets	**1 x KT small**
External diameter	**46 mm**		

KVT-ER 32

Part No.	**45452**	Mounting height	**20 mm**
EAN	**4251269318900**	Cut-out size, metric	**M32**
Package quantity	**10**	Cut-out size, round	**32,3 mm**
For max. no. of cables	**1**	Thread	**M32 × 1,5**
Max. cable diameter	**16 mm**	Thread length	**18 mm**
Color	**black**	Suitable for grommets	**1 x KT small**
External diameter	**46 mm**		

KVT-ER 50|2

Part No.	**45454**	Mounting height	**20 mm**
EAN	**4251269318917**	Cut-out size, metric	**M50**
Package quantity	**5**	Cut-out size, round	**50,4 mm**
For max. no. of cables	**2**	Thread	**M50 × 1,5**
Max. cable diameter	**16 mm**	Thread length	**20,5 mm**
Color	**black**	Suitable for grommets	**2 x KT small**
External diameter	**63 mm**		

KVT-ER 63|4

Part No.	**45456**	Mounting height	**20 mm**
EAN	**4251269318931**	Cut-out size, metric	**M63**
Package quantity	**5**	Cut-out size, round	**63,4 mm**
For max. no. of cables	**4**	Thread	**M63 × 1,5**
Max. cable diameter	**16 mm**	Thread length	**20,5 mm**
Color	**black**	Suitable for grommets	**4 x KT small**
External diameter	**75 mm**		

KVT-ER 63|1

Part No.	**45455**	Mounting height	**20 mm**
EAN	**4251269318924**	Cut-out size, metric	**M63**
Package quantity	**5**	Cut-out size, round	**63,4 mm**
For max. no. of cables	**1**	Thread	**M63 × 1,5**
Max. cable diameter	**35 mm**	Thread length	**20,5 mm**
Color	**black**	Suitable for grommets	**1 x KT large**
External diameter	**75 mm**		

icotek®

smart cable management