

QT-AT-PP □□□ □□□

QT □□□ □□□□ □ PushPull □□□□ / IP54



IP54

HL3
EN 45545-2

ECOLAB
certified

UV
ISO 4892-2A

RoHS
compliant

REACH
COMPLIANCE

Made in
Germany

QT-AT-PP □□□□ QT □□□ □□□ □□□□□ □□□□□ □□□□ □□□□ □□□ □□□□ □□□□. Pus|
QT-AT-PP□□□□ □□□□ □□□ □□□ □□□ □□□□ □□□□ □□□ □ □ □□ □□□□ □□□ □□□□ □□□ □
PushPull □□ □ add-on housing□ □□ □□ □□ □□□.

IP □□□□ (EN 60529)

IP54

□□□□□
□□□ □□□□□

UL94-V0, □□□□□


-40 C° to 100 C°

□□□ □□, □□□□□

□□ □ □□

- By utilising the QT-AT-PP grommet, connectors can be integrated directly into the cable entry frame
- □□□ □□□ □□ □□
- □□□□□ □□□
- Grommet is suitable for PushPull housings
- Cost-saving assembly

□□ □□ □ □□



EAN

□□ □□

42602
4251269323010
10
40 mm
39 mm
17 mm
2 mm